



- LoRa Gateway for ReliaGATE
- EU and NA Bands
- Long Range (15 km/10 miles)
- Thousands of End-Point Nodes
- ISM Band Scan
- Listen Before Talk
- Open Platform



Features

- LoRa Gateway for ReliaGATE** - Designed to be a companion for the ReliaGATE 10-12, expands the gateway capabilities with LoRa
- EU and NA Bands** - Supports global deployment with European 868MHz (863-870MHz) and North American 915MHz (902-928MHz) bands
- Long Range** - Covers long distances: high power radio with 15km / 10miles line of sight range (2km / 1.5miles in urban conditions); European ISM transmit power / duty-cycle limitations are supported
- ISM Band Scan** - Provides optimal performance: allows end node frequency change to improve interference rejection and dynamic link rate adaptation
- Industrial Grade** - Compact and sturdy, with reliable terminal block interfaces and a wide operating temperature range
- Open Platform** - Supported by Everyware Software Framework (ESF), the IoT Java/OSGi based-middleware for IoT Edge Gateways that accelerates gateway development and enables remote management

Description

The ReliaLORA 10-12 is a LoRa Gateway module that adds LPWAN capabilities to the ReliaGATE 10-12. Based on the Semtech SX1301 data concentrator, a multi-channel high performance transmitter/receiver, the ReliaLORA 10-12 is the fastest way to bridge an LPWAN with any cloud application; it is fully compatible with existing LoRa infrastructures. The ReliaLORA 10-12 is an industrial grade device that supports wide temperature range (-20 to +70°C) and comes in an impact-resistant ABS enclosure. Its compact design ensures simple deployment even in the most space-constraint applications. The ReliaLORA 10-12 is a global device that supports European and North America ISM bands; its long range radio reaches up to 15km / 10miles in unobstructed applications. In difficult environments, such as urban areas with multiple building its penetration reaches a radius of 2km / 1.5miles. Robust interference rejection and dynamic link rate adaptation dramatically improve performance in crowded networks; further efficiency is provided by the Listen Before Talk protocol, which allows multiple users on the same channel. The ReliaLORA 10-12 is supported by [Everyware Software Framework \(ESF\)](#), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/OSGi middleware for IoT gateways. Distributed and supported by Eurotech, ESF adds advanced security, diagnostics, provisioning, remote access and full integration with [Everyware Cloud \(EC\)](#), [Eurotech's IoT integration platform](#) (separately available).

Ordering code: RELORA-10-12-xx

XX		- 01	- 02
PROCESSOR	Data Concentrator	Semtech SX1301	
I/O INTERFACES	Exp. Connector	Yes, for Side Expansion Modules	
RADIO INTERFACES	LoRa Bands	European 868MHz (863-870MHz)	North American 915MHz (902-928MHz)
	Transmission Power	- 6 to 25 dBm	- 6 to 27 dBm
	Receiver Sensitivity	-140 dBm Max	-137 dBm Max
	Antennas (External)	1x RP-SMA	
POWER	Consumption	3W Max	
ENVIRONMENT	Operating Temp	-20 to +70°C	
	Storage Temp	-40 to +85°C	
CERTIFICATIONS	Regulatory	CE	FCC, ISED
	Safety	EN 62368, UL 60950 (§)	
	Environmental	RoHS2, REACH	
	ISM Radio	CE (RED)	FCC, ISED
	Ingress	IP40	
MECHANICAL	Enclosure	Material: ABS - Color: Aluminum	
	Dimensions	96x21x45mm (LxWxH) - With Connectors	

Software

SOFTWARE	IoT Framework	Everyware Software Framework (Java/OSGi)
-----------------	---------------	--

(§) UL, NRTL listing Factory Option.



关注我们的动态



hkaco.com



需要详细信息? 请通过sales@hkaco.com联系我们

全国免费电话: 400-999-3848

您身边的自动化专家: 广州 | 北京 | 上海 | 深圳 | 西安 | 武汉 | 成都 | 香港 | 台湾 | 美国